



Tubes

Part Number	Length (Feet)	Power (Watts)	Lumen Output	Color Temp.	Wiring ¹	AC Input ²	Terminal ³	Diffuser	DLC
Non Standard Length									
WLT810WBIXF50K	2	10	1300	5000K	Opposite	Hybrid	G13	Frosted	No
FLT813W900BIDS40K	3	13	1690	4000K	Opposite	Direct	G13	Frosted	No
ZY22W1500BINS50K ⁴	5	22	2420	5000K	Same	Direct	G13	Frosted	No
4 Foot									
Economy Series (100 lm/W)									
FLT815W1200BISS4	4	15	1500	4000K	Same	Direct	G13	Frosted	Yes
FLT818W1200BISS4	4	18	1800	4000K	Same	Direct	G13	Frosted	Yes
Standard Series (130 lm/W)									
FLT812W1200DIAB50K	4	12	1560	5000	Opposite	Hybrid	G13	Frosted	Yes
FLT815W1200BIXF4	4	15	1950	4000	Opposite	Hybrid	G13	Frosted	Yes
FLT815W1200BIXF5	4	15	1950	5000	Opposite	Hybrid	G13	Frosted	Yes
FLT818W1200BIDS40K	4	18	2340	4000	Opposite	Direct	G13	Frosted	Yes
FLT818W1200BIDS50K	4	18	2340	5000	Opposite	Direct	G13	Frosted	Yes
FLT818W1200BIDS50KC	4	18	2340	5000	Opposite	Direct	G13	Clear	Yes
FLT818W1200BISS50K	4	18	2340	5000	Same	Direct	G13	Frosted	Yes
FLT818W1200BIXF4	4	18	2340	4000	Opposite	Hybrid	G13	Frosted	Yes
FLT818W1200BIXF5	4	18	2340	5000	Opposite	Hybrid	G13	Frosted	Yes
FLT822W1200BIXF4	4	22	2860	4000	Opposite	Hybrid	G13	Frosted	Yes
FLT822W1200BIXF5	4	22	2860	5000	Opposite	Hybrid	G13	Frosted	Yes
T5									
SLDGA00424CTDT5T	4	24	3960	5000K	Opposite	Direct	T5	Clear	Yes
SLDGA00424CTDT5TFR	4	24	3960	5000K	Opposite	Direct	T5	Frosted	Yes
8 Foot									
ZST836P8FTFA850KC	8	36	4680	5000	Opposite	Direct	FA8	Clear	Yes
ZST840P8FTG1340K	8	40	5200	4000	Opposite	Direct	G13	Frosted	Yes
ZST840P8FTG1350K	8	40	5200	5000	Opposite	Direct	G13	Frosted	Yes
WLT88FT40WBIDS40FA8	8	40	5200	4000	Opposite	Direct	FA8	Frosted	Yes
WLT88FT40WBIDS50FA8	8	40	5200	5000	Opposite	Direct	FA8	Frosted	Yes

Notes:

- 1) Wiring - Same means Line and Neutral wire to the same end of the tube. Opposite means Line and Neutral wire to opposite ends of the tube.
- 2) AC Input - Direct means line voltage is connected directly to the tube (no ballast). Hybrid will work with electronic ballast or with line voltage connected directly.
- 3) Terminal - See following page for picture of G13 and FA8.
- 4) ZY22W1500BINS50K is intended for use in coolers. It has special mounting brackets for this.