

| Specifications (1X4 2X2) | | | |
|--------------------------------|----------------|----------------|----------------|
| Part Number | DMP71436W40KAE | DMP72230W40KAE | DMP72236W40KAE |
| Dimensions (Feet) | 1 X 4 | 2 X 2 | |
| Power Consumption (Watts) | 36 | 30 | 36 |
| Light Output (Lumens) | 3600 | 3800 | 5200 |
| Input Voltage (Volts) | 100-277 | | |
| Color Temperature ¹ | 4000K | | |
| Color Rendering Index | 83 | | |
| Dimmable ² | Yes | | |
| Operating Temperature | -20°C to +40°C | | |
| Certification | UL/DLC | | |
| Warranty | 5 Years | | |

| Part Numbers | |
|----------------|------------------|
| DMP71436W40KAE | 1 X 4 36W 4000K |
| DMP71436W50KAE | 1 X 4 36W 5000K |
| DMP72230W40KAE | 2 X 2 30W 4000K |
| DMP72230W50KAE | 2 X 2 30W 5000K |
| DMP72236W40KAE | 2 X 2 36W 4000K |
| DMP72236W50KAE | 2 X 2 36W 5000K |
| DMP72440W40KAE | 2 X 4 40W 4000K |
| DMP72440W50KAE | 2 X 4 40W 5000K |
| DMP72448W40KAE | 2 X 4 48W 4000K |
| DMP72448W50KAE | 2 X 4 48W 5000K |
| DMP72460W40KX | 2 X 4 60W 4000K |
| DMP72460W50KAE | 2 X 4 60W 5000K |
| DMPEBC6W | Emergency Driver |

Emergency driver provides 50% light output for a minimum of 90 minutes if power fails.

Notes:

1. 5000K also available. See part number chart
2. 0 - 10V Dimmer.
3. Surface mount and flush mount kits available